

CROSSING UNDER THE BOSPORUS

Istanbul Strait Road Tunnel Crossing Project

- > First road tunnel (3.34km) under the Bosporus
- > Single-tube, double-deck road tunnel (ID= 12m)
- > Up to approx. 100m below sea level

Challenges:

- Very large diameter TBM (Ø_{exc.}= 13.71m)
- Variable ground conditions: full face rock & soft ground with cobbles and boulders and transition zones
- Anticipated face pressures above 11 bar
- Surface access to create "safe havens" or "access shaft" no realistic option



Herrenknecht. Pioneering Underground Technologies





CONNECTION BETWEEN EUROPE AND ASIA

Istanbul Strait Road Tunnel Crossing Project


- Mixshield Slurry TBM Ø13.66m
- > Mixed face cutterhead (rock and soft ground excavation)
- Fully articulated cutterhead, accessible for atmospheric cutter change
- Full preparation for saturation diving (above ground habitat, crew shuttles, shuttle transport and transfer systems)


























ISTANBUL STRAIT ROAD TUNNEL CROSSING

Lessons learned

- Best case scenario for possible open mode chamber access in Trakaya rock sections did not happen, closed mode operation at full rated pressure was inevitable for entire tunnel length
- Investment in multi level equipment preparation for worst case conditions was key for success (accessible cutter head, cutter sensor systems, preparation for saturation diving)
- Close cooperation of all involved parties (contractor, consultants, manufacturer, divers...) starting from a conceptual design stage is mandatory
- > Full shop assembly, test and operator shop training is mandatory
- Accessible cutter head with atmospheric cutter change was key for project completion
- A trustful partnership of the complete team: Owner, Contractor and TBM supplier was the essential key to the success of such a difficult, challenging project.







WORLD RECORD IN TBM DIAMETER


Hong Kong: Tuen Mun-Chek Lap Kok Link (TM-CLKL)


- > Road tunnel for connection of the Hong Kong-Zhuhai-Macao Bridge
- > 2 x 4.2km of road tunnel by mechanized tunnelling
- Mixshield S-880, Shield-Ø17.6m
- > High pressures exceeding 5 bar associated with highly unstable ground conditions
- About 50% mixed face conditions, 50% full face alluvium




























TUEN MUN-CHEK LAP KOK LINK

AVN 3000 recovery in the tunnel, after breakthrough into reception bell



Herrenknecht. Pioneering Underground Technologies




TUEN MUN -CHEK LAP KOK LINK

Tunnel cross sections with AVN technique

- > 2x AVN3000
- > Excavation length of 10-15 meter
- > Water pressure of 5.5 bar
- Logistics in the tunnel can be maintained
- First use of TBM technology to construct cross sections under high pressures





CONCLUSION AND OUTLOOK

- Mechanized tunnelling is the first choice to construct large-diameter infrastructures underground – safely, in time and in budget.
- Large diameters require up-to-date and project-specific solutions, e.g., to master high hydrostatic pressure when crossing under rivers and straits.
- > Close and trusting teamwork tunnelling is fundamental for a project's success.
- The latest innovations underscore the high potential of future developments in mechanized tunnelling.



